



# deSIGN 42 - pre-assembled Signal Tower

## Your benefits

Thanks to its high-quality stainless steel housing, the deSIGN 42 signal tower is an ideal accompaniment to modern, design-oriented assembly lines, production facilities and machinery. The robust housing provides the key benefit of being tamper-proof for installations in public areas.

- Elegant industrial design
- Tamper-proof for public areas

## Typical applications

Fault signalling

- on machinery and equipment

Access control

- on control points in public areas

## Installation options


- Single-hole mounting
- Bracket mounting using accessories

## Features

- High-quality, robust stainless-steel housing
- Award-winning design



Size comparison deSIGN 42 / KombiSIGN 72



### Signalisation Index

|                     |   |
|---------------------|---|
| <b>Optical</b>      |   |
| LED Permanent Light | 3 |



### ❶ TECHNICAL SPECIFICATIONS/ORDER SPECIFICATIONS:

|                          | 2 tier   | 3 tier            |
|--------------------------|--|-------------------|
| Dimensions (Ø x Height): | 42 mm x 221 mm                                     | 42 mm x 255 mm    |
| Housing:                 | Stainless steel, brushed                           |                   |
| Fixing:                  | Installation mounting for Ø 22.5 mm (M22 x 1.5 mm) |                   |
| Connection:              | Cable, 2 m long, included in assembly              |                   |
| Voltage:                 | 24 V DC  | 24 V DC           |
| Current consumption:     | 50 mA per tier                                     | 50 mA per tier    |
| red/green                | <b>694 010 55</b>                                  | -                 |
| red/yellow               | <b>694 020 55</b>                                  | -                 |
| red/yellow/green         | -  | <b>694 000 55</b> |

### ✳ ACCESSORIES:

|   |                   |
|---|-------------------|
| Surface housing single                                | <b>975 109 02</b> |
| Bracket, stainless steel<br>(Protection rating IP 33) | <b>960 694 01</b> |

### ↳ TECHNICAL DIAGRAMS:

