



Base mounting



The adaptor (accessory) allows quick and simple mounting on a tube



Top view: Mounting holes integrated into the product rim allow easy mounting without having to remove the cap

Signalisation index

Multi-tone sounder 7

i TECHNICAL SPECIFICATIONS/ORDER SPECIFICATIONS:

Dimensions (Ø x Height):	89 mm x 64 mm
Housing:	PC, black
Fixing:	Base mounting, tube mounting (accessory)
Installation position:	Sound outlet facing downwards
Connection:	Screw terminal 0.5 - 1.5 mm ²
Cable entry:	Cable diameter max. 9 mm
Tone type:	Selectable, see table
Tone frequency:	See table
Life duration:	> 5,000 hrs
Duty cycle:	100 %
Voltage:	24 V AC/DC
Current consumption:	≤ 80 mA
Order No.:	133 000 75

🎵 TONE TYPES AND FREQUENCIES:

8 selectable tones and adjustable sound output

Tone	Tone type
1	Horn tone (c. 110 Hz)
2	Continuous tone (c. 3.0 KHz)
3	1 Hz tone (c. 3.0 KHz)
4	20 Hz whistle tone (c. 3.0 KHz)
5	800-970 Hz rising @ 1 Hz
6	2400-2850 Hz rising @ 7 Hz
7	1200-500 Hz falling @ 1 Hz
8	Alternating tone 800 Hz + 1200 Hz @ 1Hz

🏠 ACCESSORIES:

Adaptor for tube mounting, plastic, for tube Ø 25 mm	975 420 01
Base for tube Ø 25 mm, plastic, incl. rubber seal	975 840 90
Base for tube Ø 25 mm, metal, incl. rubber seal	975 840 91
Tube Ø 25 mm, all anodized aluminium	
100 mm	975 845 10
250 mm	975 840 25

📏 TECHNICAL DIAGRAM:

