



Surface housing (accessory)



Bracket (accessory)

**i TECHNICAL SPECIFICATIONS/ORDER SPECIFICATIONS:**

<b>Dimensions</b> (Ø x Height):	72 mm x 40 mm (Protrusion from panel)		
<b>Housing:</b>	PC/ABS-Blend; Cap: PC		
<b>Sound output:</b>	Max. 100 dB (sound output is adjustable on rear side when mounted)		
<b>Fixing:</b>	Installation mounting for Ø 22,5 mm (M22) with anti-twist device		
<b>Connection:</b>	Connector plug with screw terminal max. 1.5 mm <sup>2</sup>		
<b>Life duration:</b>	> 5,000 hrs		
<b>Voltage:</b>	24 V AC/DC	115 V AC	230 V AC
<b>Current consumption:</b>	80 mA	40 mA	40 mA
<b>Order No.:</b>	110 000 75	110 000 67	110 000 68

**🎵 TONE TYPES AND FREQUENCIES:**


8 tones selectable on rear side of the housing

🎵 position 0		1.6 kHz	86 dB (A)
🎵 position 1		1.6 kHz	86 dB (A)
🎵 position 2		1.6 kHz	86 dB (A)
🎵 position 3		1.6 kHz	88 dB (A)
🎵 position 4		3.4 kHz	90 dB (A)
🎵 position 5		3.4 kHz	100 dB (A)
🎵 position 6		3.4 kHz	96 dB (A)
🎵 position 7		3.4 kHz	100 dB (A)

**🏠 ACCESSORIES:**

Bracket with protective cap (IP 54)	975 109 01
Surface housing IP 65 (single)	975 109 02
Surface housing IP 65 (double) for 1 installation beacon and 1 Installation siren	975 109 03
Surface housing IP 65 (triple) for 2 installation beacons and 1 Installation siren	975 109 04

**📏 TECHNICAL DIAGRAM:**



**Signalisation index**

Multi-tone sounder	5
--------------------	---

