



Bulb change via removal of lens (LED bulb as accessory)



Accessories

Signalisation index	
Permanent Light	 2

i TECHNICAL SPECIFICATIONS/ORDER SPECIFICATIONS:

Dimensions (Ø x Height):	57 mm x 69 mm (Protrusion from panel)
Housing:	PA-GF, high impact
Lens:	PC, transparent Ring: PC
Connection:	Spades 6.3 mm x 0.8 mm Finger-proof model according to BGV A2, when used with insulated spades
Fixing:	Installation mounting for Ø22.5 mm (M22 x 1.5 mm) with anti-twist device
Operating voltage:	Max. 48 V
Bulb socket:	BA15d, 7 Watt max.
Bulb change:	Via removal of lens
Nut and seal included in assembly. Bulb not included in assembly.	
Voltage:	12-48 V
red	216 100 00
green	216 200 00
yellow	216 300 00
clear	216 400 00
blue	216 500 00

ACCESSORIES:

Bulb BA15d, total length 54 mm			total length 42 mm
Voltage:	12 V AC/DC (7 W)	24 V AC/DC (7 W)	30 V AC/DC (5 W)
	955 015 34	955 015 35	955 840 32
LED bulb BA15d, total length 42 mm			
Voltage:	24 V AC/DC		
Current consumption:	< 45 mA		
red	956 100 75		
green	956 200 75		
yellow	956 300 75		
clear	956 400 75		
blue	956 500 75		

TECHNICAL DIAGRAM:

