# System **Techno**

The Techno protective fence system, Ø3 mm wire, Ø4 mm wire and INOX Ø3mm wire was created to help all customers determine the hazardous areas to provide a solution with steel material that is cost effective and easy to install.

This product is made with self-supporting grid panels, with a mesh size that improves visibility to the machine that stands behind the fence.





#### Cheap

The costs are minimized because it is made as a self-supporting fence.

#### **Modularity**

All components are modular; so the same panels can be used both as fixed elements and with the help of a Kit, as a double or sliding door.

#### Visibility

The innovative system of the 32x67 (wirenetting) improves the vision of the machinery inside the restricted area.



#### Modification on place during installation

This system has the big advantage to be changed on place, with the use of a few Tools and it does not have to be repainted afterwards.






The QUICK TECHNO kit is an instrument designed exclusively to reduce assembly time, it is possible to install this 3-prolongation kit by a single installer.

The system complies with the applicable regulations.

A fundamental requirement for permanent guards is their fixing, which must be obtained with systems that require the use of tools for opening them and, as far as possible, they must not be able to remain in their place in the absence of their fixing means.


At the end of the operations therefore the kit must necessarily be removed.





### System **Techno**

#### Convex corners kit




With this accessory you can realize Internal angle of 90°.

#### Panel inclination kit



With this accessory you can make angle connections with inclinations of 30° to 180°.

#### Panel fixing kit 1 fold



This accessory allows you to be able to fix the panel to the posts later, after having changed or shortened it horizontally.

#### Leveling kit



This kit allows the leveling of the post. Ideal for setting the door posts.


#### Posts 40x40



#### Posts 40x80







#### Unlosable screw set

The new Machinery Directive requires that "fastening systems must remain attached to the fences or to the machine when removing the protections".

The screws must not be missed unless the panel or panels need to be removed for normal maintenance and it is not possible to act on the access already provided (doors).

The standard UNI EN 14120 states: Movable protective equipment, if access frequency is high (more than once a week) or if removal of the fixed guard may be difficult, a movable guard with lock must be provided.

In accordance to current regulations, the set of non-removable screws is easy to install and it is always provided.

#### Intermediate screw kit



This kit contains 6 plates and corresponding screws for H 2000 8 plates and corresponding screws for

#### Angle screw kit




This kit contains 6 plates and corresponding screws for H 2000 8 plates and corresponding screws for


## Terminal screw kit



This kit contains 3 plates and corresponding screws for H 2000 4 plates and corresponding screws for H 2520.



#### System Techno wire Ø3



Floor light 160 mm for panels - 100 mm for doors

