

AndonWIRELESS / Andon product

AndonWirelessBOX 5-Button 868 MHz



Part No.: 860.000.18



MECHANICAL DATA	
Length	193 mm
Width	66 mm
Height	35 mm
Materials	PC PC/ABS
Housing colour	Black Grey
Protection category	IP30
Type of fixing	Wall mounting
Working temperature minimum	0°C
Working temperature maximum	+40°C
Weight with packaging	529 g
Product weight	377 g

ELECTRICAL DATA	
Operating voltage	115-230V
Operating voltage type	AC
Operating voltage frequency	50Hz at 230V 60Hz at 115V
Operating voltage tolerance	+/- 10%
Rated operational voltage	230 VAC
Rated operational current	500 mA
Protection class	Protection class 2
Pollution degree	2
Overvoltage category	II
Isolation voltage	Ui = 250V; Uimp = 2.500V
Radio range max.	300 m
Radio transmission power	10 dBm at 50 Ohm
Radio frequency min/max	868.000 MHz 868.600 MHz
Radio channels	6
connectivity	USB

APPROVAL DATA		
Conforms with CE	yes	
WEEE	yes	
Conforms with RED directive	Yes	
Conforms with CCC	no	
Conforms with UL	nein	
Conforms with FCC	no	

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.





AndonWIRELESS / Andon product

AndonWirelessBOX 5-Button 868 MHz

Conforms with IC	No
EAC Zertifikat vorhanden	no
Conforms with AS-I	no
Conforms with GL	no
Conforms with RoHS CN	10 years
Conforms with VdS	no

DRAWING





For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.