

Data sheet

060PM6S2

Pendant push-button station with 6 2-speed push-buttons and emergency stop push-button, 1 N.C.



Features

Range	060 Safety Control Devices
Product	Pendant push-button stations
Type	Pendant push-button stations, 6 operators + emergency
Item code	060PM6S2
Description	Pendant push-button station with 6 2-speed push-buttons and emergency stop push-button, 1 N.C.
Colour	Yellow
Weight - gr	860,000
Custom tariff no.	8537109899
GTIN	8052878051617

Technical data

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-15° ÷ +80° C
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Mechanical durability	500.000 Operations
Enclosure material	ABS Acrylonitrile butadiene styrene
Flexible cable pipe	Suitable for cable D.8÷17mm
Rated insulation voltage	Ui 300V - Uimp 2.5KV (EN-IEC60947-1)
Electrical ratings	AC15: Ue 250V max AC, Ie 4A max, 1000VA
Mechanical interlock	yes, between opposite direction pushbuttons
Warranty period	18 months

Data sheet

060PM6S2

Pendant push-button station with 6 2-speed push-buttons and emergency stop push-button, 1 N.C.

Technical drawings

