

## Data sheet

### 080R200-GP1

Pendant push-button station, remote control, 1 hole, yellow



## Features

Range	080 Thermoplastic Push-Button Boxes, Enclosures
Product	Pendant push-button stations, remote control 200x83 mm
Type	With 1 hole Ø 22
Item code	080R200-GP1
Description	Pendant push-button station, remote control, 1 hole, yellow
Colour	Yellow RAL1003 / Grey RAL7035
Weight - gr	220,000
Custom tariff no.	85381000
GTIN	8052878066079

## Technical data

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1
Operating temperatures	-40° ÷ +80° C
Protection degree	IP66 - IPx9 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Cable clamp screw	Tightening torque 1.5Nm (13.3 Lb-in) max.
Pendant fixing ring	Stainless steel AISI 304
Flexible cable gland	M20x1.5 suitable for cable D.6÷12mm
Rated insulation voltage	Ui 300V - Uimp 2.5KV (EN-IEC60947-1)
Overvoltage category	Class II (IEC-EN61140)
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(EN-IEC 60695-2-11)
Fitted for outdoor application	yes
Pushbutton and electrical contacts block	See 020 product range: 020 SM2 D.22mm
Warranty period	18 months

## Data sheet

080R200-GP1

Pendant push-button station, remote control, 1 hole,  
yellow

---

## Technical drawings

---

