

Data sheet

080R200-GP4C

Pendant push-button station, remote control, 3+1 holes,
yellow



Features

| | |
|-------------------|--|
| Range | 080 Thermoplastic Push-Button Boxes, Enclosures |
| Product | Pendant push-button stations, remote control 200x83 mm |
| Type | With 4 holes Ø 22 |
| Item code | 080R200-GP4C |
| Description | Pendant push-button station, remote control, 3+1 holes, yellow |
| Colour | Yellow RAL1003 / Grey RAL7035 |
| Weight - gr | 220,000 |
| Custom tariff no. | 85381000 |
| GTIN | 8052878051846 |

Technical data

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1 |
| Operating temperatures | -40° ÷ +80°C |
| Protection degree | IP66 - IPx9 (IEC-EN60529) |
| Protection against impact | IK08 (IEC-EN62262) |
| Housing material | High impact grade thermoplastic polymer |
| Manufacturing process | Injection moulding |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Tightening torque | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in) |
| Cable clamp screw | Tightening torque 1.5Nm (13.3 Lb-in) max. |
| Pendant fixing ring | Stainless steel AISI 304 |
| Flexible cable gland | M20x1.5 suitable for cable D.6÷12mm |
| Rated insulation voltage | Ui 300V - Uimp 2.5KV (EN-IEC60947-1) |
| Overvoltage category | Class II (IEC-EN61140) |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(EN-IEC 60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton and electrical contacts block | See 020 product range: 020 SM2 D.22mm |
| Warranty period | 18 months |

Data sheet

080R200-GP4C

Pendant push-button station, remote control, 3+1 holes,
yellow

Technical drawings

