

Data sheet

080F0808-PR

Wall-mounting guarded push-button 84x84, Ø 22, red



Features

Range	080 Thermoplastic Push-Button Boxes, Enclosures
Product	Assembled push-button enclosures 84x84 mm
Type	Guarded push-button, red, wall-mounting
Item code	080F0808-PR
Description	Wall-mounting guarded push-button 84x84, Ø 22, red
Colour	Red
Weight - gr	72,000
Custom tariff no.	85371098
GTIN	8052878063726

Technical data

Approvals	CE
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25° ÷ +70°C
Protection degree	IP66 - IPx9 (IEC-EN60529)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Tightening torque	0.8 ÷ 1.2Nm (7.1 ÷ 10.6 Lb-in)
Overvoltage category	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(EN-IEC 60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items 020PIN-020PIR-020SMAN-020GE10
Warranty period	18 months

Data sheet

080F0808-PR

Wall-mounting guarded push-button 84x84, Ø 22, red

Technical drawings

